

Sleeve Sealing and Shrink Wrapping Machine



BSF-6030XI+BS-6040L
Fully Automatic version



TF6540SA+BS-5540M
Semi Automatic version



Packncode Systems

Head Office : A-901, Raj Maximus, Santoshi Mata Road, Off L. M. Road, Near Raj Anmol III, Borivali (West), Mumbai - 400 103.
Admin Off.: Unit No. 112, Nikisha Industrial. Estate, Pandurang Wadi, Near Lodha Aqua, Off. Western Express Highway,
Mira Road (East), Thane - 401 107. Tel : +91 22 28935740 / 28915266

E-mail : support@packncode.in / support@packncode.com Web : www.packncode.in / www.packncode.com

Always Quality Assured & Cost Effective...



Description:

TF6540SA semiautomatic sleeve sealing Machine can be pushed manually or pneumatically. After the process of sealing & cutting, the products enter the shrink tunnel automatically.

Features:

The machine is suitable for shrink packing both single object and combined objects

Application:

1. Shrink packing for many industries, such as printing, pharmacy, beverage, beer etc.

Parameters: TF-6540SA	
Voltage (V/Hz)	AC 220/50 110/60
Power (kw)	1.5
Max. Packing size (mm)	550x400x380
Max. Sealing Length(mm)	650
Working Air Pressure (kgf/cm ²)	5-7
External Dimension (LxWxH) (mm)	925x1040x1920
Net Weight (kg)	300

Description:

BSF - 6030XI + BS-6040 automatic sleeve sealing machine with shrink tunnel is designed for packing single product or combined products without tray, the equipment can be connected with the production line to complete feeding, film wrapping, sealing & cutting, shrinking and cooling automatically. There are various packing modes available. For combined object, the bottle quantity can be 6,9,12,15,18,20 or 24 etc.

Features:

1. BSF-6030XI automatic sleeve sealing machine is designed based on advanced technology and artwork introduced from abroad to ensure stability and reliability of equipment.
2. Adopt Mitsubishi PLC to achieve light, mechanical, electrical and instrumental integration.
3. The conveying belt can be set for feed-in or right feed-in as required.
4. Adopt specially-designed sealing cutter for perfect sealing without cracking or film stuck to the cutter, the conveying belt is made from "LEPOM", characterized by toughness.
5. The machine can pack 2,3 or 4 rows of bottles with or without tray. Only need to turn the switchover switch on the panel when you want to change the packing mode.
6. Adopt the worm gear reducer, which ensures the stable conveying and film feeding.

Description:

BSF - 6030XI + BS-6040 automatic sleeve sealing machine with shrink tunnel is designed for packing single product or combined products without tray, the equipment can be connected with the production line to complete feeding, film wrapping, sealing & cutting, shrinking and cooling automatically. There are various packing modes available. For combined object, the bottle quantity can be 6,9,12,15,18,20 or 24 etc.

Features:

1. BSF-6030XI automatic sleeve sealing machine is designed based on advanced technology and artwork introduced from abroad to ensure stability and reliability of equipment.
2. Adopt Mitsubishi PLC to achieve light, mechanical, electrical and instrumental integration.
3. The conveying belt can be set for feed-in or right feed-in as required.

Parameters: BSF - 6030XI	
Voltage (V/Hz)	3 Phase 380/50
Compressed Air (kg/cm ³)	7.0
Power (kw)	2
Max. Packing size (LxWxH) (mm)	500x300x330
Sealing & Cutting Size (LxH)(mm)	700x330
Packing Speed (pcs/min)	12-14
Infeed conveyor Height (mm)	850+50
Film Used	PVC, PE
External Dimension (LxWxH)(mm)	1360x2120x1900

Application:

BSF-6030XI+BS-6040 automatic sleeve sealing machine with shrink tunnel is suitable for shrink packaging of the beverage, beer, mineral water, pop-top cans and glass bottles etc without tray.

Description:

This kind of shrink tunnel is designed in hot-wind & upper-cyclone structure. It is suitable for heat shrinkable film such as PVC, POF, PP etc, specially for PE.

Features:

1. Intelligence temperature control and strong turbine motor are adopted.
2. Stainless steel mesh type conveyor and roller type conveyor are available.

Application:

BS-55 Series shrink tunnel are suitable for packing single large object or combined object consisting of several small articles.

Parameters: BS-5540M	
Voltage (V/Hz)	380/50 220/60 (3 phase)
Power (kw)	15/21
Loading (kg)	40
Conveying Speed (m/min)	0-8
Tunnel Size (LxWxH) (mm)	1450x550x400
External Dimensions (LxWxH)	