

Semi/Fully-Automatic Strapping Machine



FP-A2



- Easy to Use and Maintain
- Heavy - Duty
- Extra Safe



Packncode Systems

Head Office : A-901, Raj Maximus, Santoshi Mata Road, Off L. M. Road, Near Raj Anmol III, Borivali (West), Mumbai - 400 103.

Admin Off.: Unit No. 112, Nikisha Industrial Estate, Pandurang Wadi, Near Lodha Aqua, Off. Western Express Highway, Mira Road (East), Thane - 401 107. Tel : +91 22 28935740 / 28915266

E-mail : support@packncode.in / support@packncode.com Web : www.packncode.in / www.packncode.com

Always Quality Assured & Cost Effective...

Semi Automatic Box Strapping Machine

Features

- Instant heating in only 20 seconds
- Durable electro - magnetic clutch transmission increases motor life, strapping speed and reduce overall machine noise
- The unique design of control switch, independent PCB control for feeding & heating make the unit maintenance friendly
- One touch machine operation energy saving mode activates within 1.5 sec of non-use and allows for instant operation
- Stainless steel frame is available for strapping moisturized



FP- B2



KZA - 8060

Model	FP 90 / FP 90 L	FP-96	FP- A2	FP - B2	KZA - 8060
Strapping Speed	1.5 Seconds/ Strap	1.5 Seconds/ Strap			1.5 Seconds/Strap
2.15 sec/turn					
Strapping Force (adjustable)	60 kg.	60 kg.	60 kg		50-700N
Strap width	9.15 mm	9.15 mm	9-15mm		9-15mm
Power Supply & Consumption	220v, 50/60 Hz, 0.65 KW				220V 50/60Hz,
	220 v, 50H, 850w		Single Phase	1/4 HP	
Dimensions (mm)	895 x 565 x 735 (LxWxH)		1570 x 565 x 480		750 x 550 x 750



FP-90L

Automatic Strapping Machine

Features

- Fast strap change: Front loading and inserting of strap for convenient service
- Ergonomic Design: Provides comfortable and safe operation for various sizes, shapes and materials of straps.
- Fast Strapping: Strapping is quickly accomplished in only 1.5 seconds
- Simplified Structure: Makes unit easy to operate and maintain
- Safety: The spool dispenser is built inside the machine CE certified electronic components ensure dependable control

W H	650	850	1050	1250	1450	1650	1850	2050	2250	2450
400	●	●	●	●	●	●	●	●	●	●
600	●	S	●	●	●	●	●	●	●	●
800	●	●	●	●	●	●	●	●	●	●
1000	●	●	●	●	●	●	●	●	●	
1200										
	●	●	●	●	●	●	●	●		



FP-118



FP- 600

Model	FP 118 Automatic	FP 600 Pallet Semi Automatic
StrappingSpeed:	30 Straps /min	2.5 Sec / Strap
Machine Tension	10 -70 kg	5 - 60 kgs
Strap width:	9-15 mm (PP or PE)	12 - 15mm (PP or PE)
Power: 1 Phase	AC, 220v, 50 /60 Hz	0.4kwAC, 220v, 50/60Hz0.3kw
Weight:	142 kg	80kg

Table - Type Semi Automatic Strapping Machine

Model	FPT
Voltage	AC 220 / 50 110 /60
Power Consumption	90 W
Max. Strapping Size (W x H) (mm)	Not Stipulated
Min. Strapping size (W x H) (mm)	60 x 15
Strapping speed	1.8 Sec / Strap
Width of Strapping Belt (mm)	6 -10
Dimension (L x W x H) (mm)	665 x 355 x 200
Net Weight	18 kg

Features:

Model FPT is suitable for packing small packs such as bank notes, financial documents, parcel post press work and gift etc. It is widely used in different fields such as post office, bank and book store.



FPT